
CJ2 Series


Dimensions of Accessories (Options)

Single Knuckle Joint Material: Rolled steel



								mmj
Part no.								
I-J010C								
I-J016C	16	8	25	M5 x 0.8	5 ^{+0.048}	6.4	12	14


Double Knuckle Joint Material: Rolled steel



								[HIIII]
Part no.	Applicable bore size	Αı		L	ī	-1		MM
Y-J010C	10	8	15	5.2	21		M4 x 0.7	
Y-J016C	16	11	16	6.6	6.6 21		M	5 x 0.8
Part no.	NDd9	NDH	10	0 N		F	1 1	U₁
Y-J010C	$3.3^{-0.030}_{-0.060}$	3.3+0.	048	3.	2	8	3	10
Y-J016C	5-0.030	5 ^{+0.048}		6.5		12		10

^{*:} A knuckle pin and retaining rings are included.

Knuckle Pin Material: Stainless steel



CJ1

CJP CJ₂ **JCM**

CG1

CG3 JMB

MB

MB1

CA2


CS₁

CS2

								[mm]	JCM
_	Annlirahla		٦.					Included	-
Part no.									CM2
CD-J010	10	3.3-0.030	3	15.2	12.2	1.2	0.3	Type C 3.2	
IY-J015	16	5-0.030	4.8	16.6	12.2	1.5	0.7	Type C 5	СМЗ
									1


- *: For ø10, a clevis pin is diverted.
- *: Retaining rings are included with a knuckle pin.

Double Knuckle Joint (With One-touch Connecting Pin)



									[mm]
Part no.	Applicable bore size	A 1	Lı	ММ	NDd9	NDH10	NX	Rı	U ₁
Y-J10	10	8	21	M4 x 0.7	3.3-0.030	3.3+0.048	3.2	8	10
Y-J16	16	11	21	M5 x 0.8	5-0.030 5-0.060	5 ^{+0.048}	6.5	12	10

One-touch Connecting Pin for Double Knuckle Joint Material: Stainless steel






Part no. IY-J10 IY-J16 5-0.03

Mounting Nut

Material: Carbon steel



					[mm]
Part no.	Applicable bore size	B ₁	C ₁	d	H ₁
SNJ-006C	6	8	9.2	M6 x 1.0	4
SNJ-010C	10	11	12.7	M8 x 1.0	4
SNJ-016C	16	14	16.2	M10 x 1.0	4
SNKJ-016C*	16	17	19.6	M12 x 1.0	4

^{*:} For ø16 non-rotating type. (Use SNJ-016C for ø10 non-rotating type.)

Rod End Nut

Material: Carbon steel



					liiiiii
Part no.	Applicable bore size	B2	C ₂	d	H ₂
NTJ-006B	6	5.5	6.4	M3 x 0.5	2.4
NTJ-010C	10	7	8.1	M4 x 0.7	3.2
NTJ-015C	16	8	9.2	M5 x 0.8	4


-X□ Technical Data

D-□



CJ2 Series

Pivot Bracket (T-bracket)



Part no.	Applicable bore size	тс	TDH10	тн	тк	TN	TT	ΤU	τv	TW	тх	ΤY	TZ
CJ-T010C	10	4.5	3.3+0.048	29	18	3.1	2	9	40	22	32	12	8
CJ-T016C	16	5.5	5 ^{+0.048}	35	20	6.4	2.3	14	48	28	38	16	10


*: A T-bracket includes a T-bracket base, single knuckle joint, hexagon socket head bolt and spring washer.

[mm]

*: For dimensions of (U) and (S + Stroke), refer to the double clevis drawing on page 60.

Clevis Pin


Material: Stainless steel



								[mm]
Part no.	Applicable bore size	Dd9	d	L	Lı	m	t	Included retaining ring
CD-J010	10	3.3-0.030	3	15.2	12.2	1.2	0.3	Type C 3.2
CD-Z015	16	5-0.030	4.8	22.7	18.3	1.5	0.7	Type C 5
CD-JA010*	10	3.3-0.030	3	18.2	15.2	1.2	0.3	Type C 3.2

- *: For ø10 double clevis type, with air cushion and built-in speed controller.
- *: Retaining rings are included with a clevis pin.

One-touch Connecting Pin for Double Clevis Material: Stainless steel




							[mm]			
Part no.	Applica bore si			Dd9	н	L	w			
CD-J10	10		3.	3-0.030	13.4	13.2	4			
CD-J16	16		4)	5-0.030 -0.060	18.2	19.5	5			
Part no.	W 1	W	1 2		N	Note				
CD-J10	12	1	5			mounted on cylinders with air				
CD-J16	15	1	8	cushion, or rail mounting type auto switches.						

^{*:} Please pay attention to the applicable cylinder.

Rod End Cap

Material: Polyacetal

Flat type/CJ-CF□□□









									[mm
Part no.		Applicable	Α	D		мм	N	ь	w
Flat type	Round type	bore size	^	ייו	-	IVIIVI	IN	n	٧٧
CJ-CF006	CJ-CR006	6	6	8	11	M3 x 0.5	5	8	6
CJ-CF010	CJ-CR010	10	8	10	13	M4 x 0.7	6	10	8
CJ-CF016	CJ-CF016 CJ-CR016		10	12	15	M5 x 0.8	7	12	10

Mounting Brackets, Rod End Brackets, and Nut Material: Stainless Steel

Part No. (Dimensions: Same as standard type)

					,			
	Bore size [mm]	Foot	Flange	Single knuckle joint	Double knuckle joint*	Mounting nut	Rod end nut	
	10		_	I-J010SUS	Y-J010SUS	_	NTJ-010SUS	
16 0		CJ-L016SUS	CJ-F016SUS	I-J016SUS	Y-J016SUS	SNJ-016SUS	NTJ-015SUS	

 $[\]ast \text{:} \ A \ \text{knuckle} \ \text{pin} \ \text{and} \ \text{retaining} \ \text{rings} \ \text{are shipped} \ \text{together}.$