

Made to Order Common Specifications: -XC24: With Magnetic Shielding Plate -XC25: No Fixed Throttle of Connection Port



30 With Magnetic Shielding Plate -XC24

Symbol

Shields against the magnetic leaked from external slider.

Applicable Series


Series	Description	Model	Action	Vol. no. (for std model)
CY3	Magnetically coupled rodless cylinder	CY3B	Double acting	②-1 From P. 1468
REA	Sine rodless cylinder	REA	Double acting	②-3 From P. 25

How to Order

CY3B
REA Standard model no. -XC24
 With magnetic shielding plate ↓

Specifications: Same as standard type

Dimensions



Dimensions	Bore size (mm)								
	ø6	ø10	ø15	ø20	ø25	ø32	ø40	ø50	ø63
□B	19	27	37	38	48	62	72	88	102
Standard external (□B)	17	25	35	36	46	60	70	86	100

* Dimensions except mentioned above are the same as standard type.
* REA is ø25 to ø63.

31 No Fixed Throttle of Connection Port -XC25

Symbol

Type with no restrictor on the port, since it's using air-hydro type on the rod cover and the head cover of air cylinder CM2 series.

Applicable Series

Series	Description	Model	Action	Vol. no. (for std model)	
CM2	Air cylinder	CM2-Z	Double acting, Single rod Single acting (Spring return/airless)	②-1 From P. 172	
		CM2W-Z	Double acting, Double rod		
		CM2K-Z	Double acting, Single rod		
	Non-rotating rod type	CM2KW-Z	Double acting, Double rod Single acting (Spring return/airless)		
		Direct mount type	CM2R-Z		Double acting, Single rod
		Non-rotating rod, Direct mount type	CM2RK-Z		Double acting, Single rod
Smooth cylinder	CM2Y-Z	Double acting, Single rod			


* Except with air cushion (Standard equipment)

How to Order

CM2 Standard model no. -XC25
 No fixed throttle in connection port ↓

Specifications: Same as standard type

Construction



* External dimensions are the same as standard CM2 series.

⚠ Caution

1. Use a shock absorber, etc.
When the piston speed exceed 750 mm/s, make sure that direct impact does not apply on the cylinder cover by using an external stopper (shock absorber, etc).